




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>G06K 9/00, A61B 1/00</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 95/30964</b> <b>(43) International Publication Date:</b> 16 November 1995 (16.11.95)
<b>(21) International Application Number:</b> PCT/US95/05669 <b>(22) International Filing Date:</b> 3 May 1995 (03.05.95) <b>(30) Priority Data:</b> 08/239,086 5 May 1994 (05.05.94) US <b>(71) Applicant:</b> SRI INTERNATIONAL [US/US]; 333 Ravenswood Avenue, Menlo Park, CA 94025 (US). <b>(72) Inventor:</b> GREEN, Philip, S.; 585 California Way, Redwood City, CA 94062 (US). <b>(74) Agents:</b> ALLEN, Kenneth, R. et al.; Townsend and Townsend Hourie and Crew, Steuart Street Tower, 20th floor, One Market Plaza, San Francisco, CA 94105 (US).		<b>(81) Designated States:</b> CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.          Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: METHOD FOR TELEMANIPULATION WITH TELEPRESENCE



## (57) Abstract

In a telemanipulation system (12) for manipulating objects located in a workspace at a remote worksite by an operator (14), such as in a remote surgical system, the remote worksite having a manipulator with an end effector (39) for manipulating an object at the workspace, a controller including a hand control (22) at the operator's station for remote control of the manipulator, an image capture device (19), and image output device (20) for reproducing a viewable real-time image, the improvement wherein a position sensor associated with the image capture device (19) senses position relative to the end effector (39) and a processor (23) transforms the viewable real-time image into a perspective image with correlated manipulation of the end effector (39) by the hand controller (22) such that the operator can manipulate the end effector and the manipulator as if viewing the workspace in true presence. Image transformation according to the invention includes translation, rotation (25) and perspective correction (29).

Best Available Copy

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

## 5 METHOD FOR TELEMANIPULATION WITH TELEPRESENCE

## BACKGROUND OF THE INVENTION

This invention relates to telemanipulation using  
telepresence, and more particularly to applications of  
10 telemanipulation to laparoscopic surgery.

A telemanipulation system allows an operator to  
manipulate objects located in a workspace from a remote  
control operator's station. For example, in a laparoscopic  
abdominal surgery procedure, the patient's abdomen is  
15 insufflated with gas, and cannulas are passed through small  
incisions to provide entry ports for laparoscopic surgical  
instruments. Laparoscopic surgical instruments include an  
image capture means for viewing the surgical field and working  
tools, such as forceps or scissors. The working tools are  
20 similar to those used in open surgery, except that the working  
end of each tool is separated from its handle by an extension  
tube. The surgeon performs surgery by sliding the instruments  
through the cannulas and manipulating them inside the abdomen  
while referencing a displayed image of the interior of the  
25 abdomen. Surgery by telepresence, that is, from a remote  
location by means of remote control of the surgical  
instruments, is a next step. A surgeon is ideally able to  
perform surgery through telepresence, which, unlike other  
techniques of remote manipulation, gives the surgeon the  
30 feeling that he is in direct control of the instruments, even  
though he only has remote control of the instruments and view  
via the displayed image.

The effectiveness of telepresence derives in great  
measure from the illusion that the remote manipulators are  
35 perceived by the operator of the system to be emerging from  
the hand control devices located at the remote operator's  
station. If the image capture means, such as a camera or  
laparoscope, are placed in a position with respect to the

manipulators that differs significantly from the anthropomorphic relationship of the eyes and hands, the manipulators will appear to be located away from the operator's hand controls. This will cause the manipulators to move in an awkward manner relative to the viewing position, inhibiting the operator's ability to control them with dexterity and rapidity. However, it is often unavoidable in applications such as laparoscopic surgery to move the laparoscope in order to obtain the best possible image of the abdominal cavity.

Thus, a technique is needed for providing to the operator the sense of direct hand control of the remote manipulator, even in the presence of a substantially displaced imaging device, such that the operator feels as if he is viewing the workspace in true presence.

#### SUMMARY OF THE INVENTION

According to the invention, in a telemanipulation system for manipulating objects located in a workspace at a remote worksite by an operator at an operator's station, such as in a remote surgical system, the remote worksite having a manipulator or pair of manipulators each with an end effector for manipulating an object at the workspace, such as a body cavity, a controller including a hand control at the control operator's station for remote control of the manipulators, an image capture means, such as a camera, for capturing in real-time an image of the workspace, and image producing means for reproducing a viewable image with sufficient feedback to give the appearance to the control operator of real-time control over the object at the workspace, the improvement wherein means are provided for sensing position of the image capture means relative to the end effector and means are provided for transforming the viewable real-time image into a perspective image with correlated manipulation of the end effector by the hand control means such that the operator can manipulate the end effector and the manipulator as if viewing the workspace in substantially true presence. By true presence, it is meant that the presentation of an image is a true perspective image

simulating the viewpoint of an operator. Image transformation according to the invention includes rotation, translation and perspective correction.

5 The invention will be better understood by reference to the following detailed description in connection with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

10 Fig. 1A is a side view of a remote operator station and of a worksite station in a telemanipulation system according to the present invention.

15 Fig. 1B is a perspective view of a remote operator station and a worksite station adapted for stereoscopic viewing in a telemanipulation system according to the present invention.

Fig. 2 is a diagrammatic perspective view of a specific embodiment of the invention wherein the image capture means is centered and normalized relative to the viewpoint of an operator using the manipulators.

20 Fig. 3 is a diagrammatic perspective view of a specific embodiment of the invention wherein the image capture means is laterally displaced relative to the viewpoint of an operator using the manipulators.

25 Fig. 4 is a diagrammatic perspective view of a specific embodiment of the invention wherein the image capture means is at a lower position relative to the viewpoint of an operator using the manipulators.

30 Fig. 5A is a front elevational view of the lenses of a stereoscopic image capture means where the lenses are in a normalized position relative to the viewpoint of an operator using the manipulators.

35 Fig. 5B is a front elevational view of the lenses of a stereoscopic image capture means where the lenses are rotated relative to the viewpoint of an operator using the manipulators.

Fig. 6A is a top plan view of an image of a remote manipulator in a telemanipulation system that shows a

superimposed stereographic four-point coordinate element prior to calibration.

Fig. 6B is a top plan view of an image of a remote manipulator in a telemanipulation system that shows a  
5 superimposed stereographic four-point coordinate element after calibration.

Fig. 7A is a top plan view of an image of a remote manipulator in a telemanipulation system that shows the angle of displacement in the horizontal of the image capture means  
10 relative to the manipulators.

Fig. 7B is an enlarged view of a portion of Fig. 4A that shows the combined effect on the position of the end effector of a manipulator after a lateral shift.

Fig. 8 is a geometric depiction of the image of a manipulator as a projection of a hand control.  
15

Fig. 9 is a geometric depiction of the actual manipulator whose image is depicted in Fig. 8.

#### DESCRIPTION OF SPECIFIC EMBODIMENTS

20 Fig. 1A shows a telemanipulation system 10 according to the present invention with a remote operator station 12 where an operator 14 (a surgeon, for example) can perform telemanipulation on an object at a worksite station 16. The remote station 12 includes a video display 20 for the operator  
25 14 to view the worksite and an apparent workspace 22 where the operator 14 carries out the actual manipulations by grasping hand control means 24, 26, such as surgical instrument handles, which are connected to position sensors 51, 55. The worksite station 16 includes an image capture means 19,  
30 including a sensor means 21 with camera lens 28 of a camera or endoscope and understanding that there is an image capture means 19 associated with that lens, which captures an image of an object located in the workspace 30. (An endoscope would be within the body cavity.) The manipulators 32, 34 allow  
35 manipulation of the object in the workspace 30 correlated with a displayed image by use of end effector means 39, 41.

The image captured at worksite 16 is transmitted through a number of stages which present to operator 14 a

real-time image of the object in the workspace 30. In particular, sensor means 21, including optical image capture means 19, provides a view of the manipulators 32, 34 through a camera lens 28, passing such image information via path 13 to an image processor 23. In addition, image sensor position information (camera position) may be passed on path 63 to coordinate transformer 43. (For a fixed camera, the camera position information can be preset). Further, mechanical position sensing means 59, 61 sense the position of manipulators 32, 34 mechanically, passing on the position information to coordinate transformer 43 via path 157.

The image processor 23 includes a rotation and translation means 25, a perspective correction means 29 and a calibration means 27. The rotator is for rotating the image and the translator is for shifting the rotated image. The perspective corrector 29 is primarily for magnifying the image and may include some tilt correction. The calibrator 27 may have various functions, depending upon the type of image input. It is in particular used to calibrate the image to a known reference coordinate system to enable an operator to coordinate motions of the hand controls and the manipulators. After the image has undergone transformation through one or more of these function blocks, the pixel data is passed on path 15 to an imager 31 which drives a video display 20, which in this embodiment is a monoscopic device, and data about the image is passed on to the coordinate transformer 43, whereby any processed image data potentially affecting control of the manipulators (e.g., magnification, rotation, translation) is made available for the control of the manipulators. The details of the processes which may be affected are explained hereinbelow, particularly with respect to calibration.

The coordinate transformer 43 is the principal processor of position information. Camera position information, manipulator position information, and hand control position information are received and processed therein. In particular, the positions of hand controls 24, 26 are sensed by position sensors 51, 51 and passed via path 47 to coordinate transformer 43. After transformation and

processing in coordinate transformer 43, control information is applied to position-following servo 45, which drives and controls manipulators 32, 34 with end effectors 39, 41. The operation of each of these blocks will be described in further detail.

In operation, the camera lens 28 captures the image of the object in the actual workspace 30 in a specific orientation on image capture means 19. The video display 20 displays this image so that the operator 14 can view the object as it is manipulated. The operator 14 may then grasp hand control means 24, 26 located in the apparent workspace 22 to carry out the desired manipulations. The hand control means 24, 26 at remote station 12 under instruction of the position-following servo 45 control the manipulators 32, 34 at worksite station 16, which actually manipulate the object in workspace 30. The actual workspace 30 is thus effectively projected back to the remote operator 14 to create the illusion that he is reaching and looking directly into it and controlling the object located in workspace 30. Properly projected, this results in natural and spontaneous control motions by the operator 14, even if he is located in an another room or another extremely remote location.

The problems addressed by the present invention arise from the situation where the camera lens 28 is not placed at the same position in the real workspace 30 relative to the manipulators 32, 34 as the eyes of the control operator viewing the projected image in the "apparent" workspace 22 relative to the hand control means 24, 26. A solution is provided by the present invention.

The telemanipulation system according to the present invention can also be adapted to accommodate stereoscopic viewing. Fig. 1B shows all the elements of Figs. 1A, with the addition of a second camera lens 36 and image capture means 35. The two camera lenses 28 and 36 can be separated by about 10°, which is the same interocular viewing disparity that one experiences when viewing a visual field at 40 cm separation. The stereo image is displayed on a stereo video display monitor 38 (e.g. using an electronically switched polarizer 37



over the screen) and viewed through cross-polarized stereoscopic lenses 40, thus offering a natural image to the remote operator 14 so that the operator experiences the correct visual feedback when reaching and looking directly into the actual workspace 30 and directly manipulating the object located therein. The details of the system are explained hereinafter.

Fig. 2 is a diagrammatic perspective view of the elements of the worksite station 16 in workspace 30 of the telemanipulation system, showing features of Fig. 1 which are in a control loop. The system an operator at a remote station to manipulate objects located at a centerpoint 50 in the workspace 30. In the monoscopic system, sensor means 21 with camera lens 28 and image capture means 19 captures a real-time image of the object. The operator 14 uses dual hand control means 24, 26 to control left manipulator 32 and right manipulator 34, respectively, which allow remote manipulation of the object at the workspace 30. For hand control means 24, 26 and manipulators 32, 34, there is in this example a fixed pivot point about which bidirectional angular motion can be effected, together with a telescopic-like extension capability for each of the manipulators and hand controllers. The correlation between the hand control means 24, 26 and the manipulators 32, 34, combined with the image captured by the camera lens 28, provide sufficient feedback to give the appearance to the control operator of real-time control over the object at the workspace (further improvement is possible with tactile feedback). Both left manipulator 32 and right manipulator 34 are in this example raised 30° with respect to an arbitrary plane of orientation, including a centerline axis 52 of the workspace 30, to simulate a typical positioning of an object in the real local workspace 30.

In operation, camera lens 28 is at the 0° lateral position with respect to the centerline axis 52, such that the camera lens 28 is between left manipulator 32 and right manipulator 34. The face of the camera lens 28 is raised at for example a 45° angle with respect to the plane containing centerline axis 52 and baseline 53. This camera position and

orientation is a close approximation to the actual eye position with respect to the manipulators 32 and 34 and represents a base or reference position. The image captured by the camera lens 28 appears as if the operator were looking at the centerpoint 50 while standing over the manipulators 32 and 34 with a 45° angle view into the workspace. Both left manipulator 32 and right manipulator 34 appear in the bottom of the displayed image (proximal to the operator's hand controls), evoking a strong sense of telepresence, which means that the operator senses direct control of manipulators 32 and 34, allowing control with dexterity and rapidity, particularly where there is tactile feedback from the manipulators 32, 34 to the hand control means 24, 26.

In a telemanipulation application in which positioning of elements is difficult due to obstructions, it is often necessary to move the camera lens 28 to different positions result in a different view of the object at the centerpoint 50. Referring to Fig. 3, a diagrammatic perspective view of the elements in workspace 30 of the worksite station 16 of a monoscopic telemanipulation system is shown in which the camera lens 28 position is rotated by angle  $\theta$  58 laterally in the horizontal plane away from the centerline axis 52. After rotation of the camera lens 28, left manipulator 32 and right manipulator 34 are still inclined downward at a 30° angle relative to the plane containing centerline axis 52 and baseline 53, and the camera lens 28 is still positioned at an angle  $\theta$  above the plane formed by centerline axis 52 and baseline 53. In order to evoke a sense of telepresence in the operator similar to the case in which the camera lens 28 is positioned directly over manipulators 32 and 34 (as in Fig. 2), according to the invention, the captured image projected by the camera lens 28 is rotated about visual axis 54 through the center of the camera lens 28. This compensates for rotation about "vertical" axis U to effect a static reorientation of the apparent manipulator positions.

It should be understood that camera lens 28 and image capture means 19 enjoy a full range of rotation about

vertical axis U, and that the angles relative to reference planes and the like of the manipulators and the camera are dictated by the constraints of the operating environment. Additionally, camera lens 28 may be positioned at different angles relative to the plane formed by centerline axis 52 and baseline 53. For example, Fig. 4 shows camera lens 28 positioned at an elevation of 15° above the (arbitrary) reference plane formed by centerline axis 52 and baseline 53. In this alignment, camera lens 28 is below manipulators 32, 34.

If the image is purely monoscopic as depicted in Fig. 1A, the system can effect static reorientation of the manipulators 32 and 34 about an axis 54 through a point, specifically center point 50, by rotating the digital image through rotation means 25. Fig. 3 shows the relevant angles of rotation. Angle  $\phi$  56 denotes the angle of declination of the visual axis 54 of camera lens 28 below vertical axis U. Angle  $\theta$  58 denotes the rotation of camera lens 28 position in the horizontal plane (formed by lines 52, 53) away from centerline axis 52 relative to the centerpoint 50.

Rotation means 25 effects static realignment of the manipulators by rotating the real-time image pixel-by-pixel by an angle approximately equal to  $-\theta$ , according to known methods. After this operation is complete, the left manipulator 32 and right manipulator 34 appear in the bottom of the displayed image (lower half of the projected screen). The camera lens 28 remains stationary, and the displayed image is rotated through image manipulation. Note that if hand control means 24, 26 at the operator's station are positioned above the viewpoint of the control operator, the rotation of the displayed image will correct the displayed image to the point where the manipulators appear in the top of the displayed image (upper half of the projected screen). In either case, the transformation of the displayed image allows the operator to view the manipulators as if emerging from the operator's hand controls. The remapping of the image is effected before actual control can be effected.

In addition to effecting static realignment through digital image transformation, transformation means 25 may effect dynamic synchronization of apparent manipulator tip positions with hand control positions by performing the following coordinate transformation on the video image data. The actual position of the manipulator tips in the workspace 30 can be transformed to an apparent position in the displayed image so that the manipulators will appear to move as though rigidly connected to the operator's hand controls. The altering of the apparent position of the manipulator tips improves the dexterity of the operator in handling the object in the workspace 30. Because the end point of the end effector of the manipulator is known, the point (a,b,c) can be related to the angular position and length of the manipulator, and the point (p,q,r) can be related to the same parameters relative to the hand control using well-known trigonometric relationships between vectors and their endpoints. Thus:

$$\begin{bmatrix} p \\ q \\ r \end{bmatrix} = \begin{bmatrix} \cos\theta' & \sin\theta' & 0 \\ -\sin\theta' & \cos\theta' & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \cos\phi & 0 & \sin\phi \\ 0 & 1 & 0 \\ -\sin\phi & 0 & \cos\phi \end{bmatrix} \begin{bmatrix} \cos\theta & \sin\theta & 0 \\ -\sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \end{bmatrix} \quad (\text{Eq. 1})$$

In connection with the transformation associated with the above equation, the image is rotated by an angle  $\theta'$  selected by the operator to bring the apparent position of the manipulators into substantial registration with the hand controls. It is an observation that angle  $\theta' \approx -\theta$ . This transformation describes the relationship between the position of the point represented by the end effector means at (a,b,c) (for either end effector means) relative to the point (p,q,r) of the corresponding tip of the manipulator in the apparent workspace in the displayed image on video display 20.

Another method of achieving static reorientation of manipulator positions is to rotate the image capture means about its visual axis. Referring again to the monoscopic system depicted in Fig. 1A and Fig. 3, camera lens 28 is rotated about its own visual axis 54, an axis normal to the plane of the camera lens 28, to the point where left manipulator 32 and right manipulator 34 appear in the bottom

of the displayed image (lower half of the projected screen). Note again that if hand control means at the operator's station are positioned above the viewpoint of the control operator, the rotation of camera lens 28 and image capture means 19 will correct the displayed image to the point where the manipulators appear in the top of the displayed image (upper half of the projected screen).

To preserve the stereoscopic effect, in the case of stereoscopic imaging, as depicted in Fig. 1B, rotations cannot be done about separate axes through each camera lens, but (referring to Fig. 5A and Fig. 5B) must be done in concert about a single axis offset from either lens. Specifically, rotation is done normal to center axis 57 passing through the centerpoint 50 and an arbitrary point on center axis 57 between the stereoscopic camera lenses 28 and 36 (Fig. 5A & 5B). This axis is similar to the visual axis 54 described in connection with Fig. 2. Referring to Fig. 5A, the lenses of a stereoscopic device are shown in their initial position. Center axis 57 shows the fixed relation of each lens of the camera pair and is parallel to a reference axis 59 parallel to an axis in the plane formed by manipulators 32, 34 intersecting at the centerpoint 50, where the axis is normal to a line bisecting the manipulators and passing through the centerpoint 50. In order to reorient the displayed image through rotation of the image capture means, center axis 57 is canted relative to a reference plane 59 passing through centerpoint 50, which plane includes reference axis 59, as shown in Fig. 5B.

There is a limitation on the amount of visually acceptable rotation of the stereoscopic image capture means 19, 35 and the elevation of the image capture means 19, 35 relative to the plane of the manipulators 32, 34. The elevation cannot be so great as to make it impossible to change the relative view angle of each of the two manipulators relative to one another. Clearly, if angle  $\phi$  equals  $90^\circ$  elevation (where the viewing axis 54 lies in the reference plane formed by lines 52 and 53), no useful change in the relative view angle will be achieved by rotating the image.

At other angles of elevation, the limitation depends on the separation angle of the manipulators 32, 34 and secondarily on the separation of the stereoscopic lenses 28, 36.

5 In addition to achieving static reorientation of manipulator positions by rotation of the camera lens 28, the system can effect a dynamic realignment by performing a coordinate transformation through translation means 25. The actual position of the manipulator tips in the workspace 30 can be transformed to an apparent position in the displayed  
10 image so that the manipulators will appear to move as though rigidly connected to the operator's hand controls. The altering of the apparent position of the manipulator tips improves the dexterity of the operator in handling the object in the workspace 30.

15 Fig. 8 and Fig. 9 depict the image 132 of a manipulator (32) and an actual manipulator 32, respectively, relative to a hand control 24. In this example, and comparing Fig. 2, manipulators and corresponding controllers represented by hand controls are of a type utilizing a single pivot point  
20 151, 161 in connection with the position sensors 51, 61 with two dimensional pivot about the point(s) and extension along the axis of the manipulator 32. Other motions consistent with these actuations, such as longitudinal rotation of the manipulator about its axis is contemplated by the invention.  
25 With reference to Fig. 8 and Fig. 9, movement of the hand control 24 causes the manipulator tip 72 to move to a new point (a,b,c) in workspace 30 such that the image 132 of the manipulator tip 172 moves to a new point (p,q,r) in the apparent workspace 22, that point appearing in the view of the  
30 operator to be at the extended end of the hand control 24. It may be preferable to express the servo commands relating the hand control and the corresponding manipulator in their polar coordinate systems ( $\Omega$ ,  $\psi$ , L) and ( $\Omega'$ ,  $\psi'$ , L'). These polar coordinates and their respective points in Cartesian  
35 coordinate systems are related by well-known polar to Cartesian transformations.

Referring again to Fig. 3, the specific angles of rotation used in calculating the coordinate transformation are

shown. Angle  $\Phi$  56 denotes the angle of declination of the visual axis 54 of camera lens 28 below vertical axis U. Angle  $\Theta$  58 denotes the rotation of camera lens 28 in the horizontal plane away from centerline axis 52 relative to the centerpoint 50 in the workspace 30. Angle  $\Gamma$  60 denotes the rotation of camera lens 28 about its visual axis 54.

In operation of a monoscopic telemanipulation system, camera lens 28 and image capture means 19 are rotated about visual axis 54 as described above. The coordinates (a,b,c) in a reference orthogonal Cartesian coordinate system of the three-dimensional workspace 30 define the actual position of the tip of a manipulator, such as left manipulator 32. The following matrix equation relates the desired apparent position (p,q,r in orthogonal Cartesian space) of the manipulator tip in the displayed image in video display 20 to the actual position (a,b,c) of the manipulator tip in the workspace 30:

$$\begin{bmatrix} p \\ q \\ r \end{bmatrix} = \begin{bmatrix} \cos\Gamma & \sin\Gamma & 0 \\ -\sin\Gamma & \cos\Gamma & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \cos\Phi & 0 & \sin\Phi \\ 0 & 1 & 0 \\ -\sin\Phi & 0 & \cos\Phi \end{bmatrix} \begin{bmatrix} \cos\Theta & \sin\Theta & 0 \\ -\sin\Theta & \cos\Theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \end{bmatrix}$$

(Eq. 2)

When the manipulator tip is displayed at a position (p,q,r) in the displayed image in video display 20, the manipulator will appear to the operator as if it is actually at the end of the operator's rigid hand control device. The coordinate transformation improves the ease with which the operator can handle objects in the workspace using a telemanipulation system.

In the case of stereoscopic imaging, the stereo image capture means 19, 35 is rotated relative to a reference axis 59 parallel to an axis in the plane formed by manipulators 32, 34 intersecting at the centerpoint 50, where the axis is normal to a line bisecting the manipulators and passing through the centerpoint 50, as shown in Fig. 5B. Angle  $\Gamma$  60 measures the amount of rotation of the stereoscopic lenses 28, 36, and its value can be used in Eq. 2 to calculate the proper coordinate transformation for stereoscopic viewing.

In order to ensure that the movements of the manipulators 32, 24 in workspace 30 properly track the movements of the hand controls 24, 26 in the operator's apparent workspace 22 even without complete knowledge of all angles and positions, the operator can establish a calibration reference for manipulators 32, 34 as they are viewed in the displayed image in video display 20 in connection with the position-following servo. Referring to Fig. 6A, which shows the image displayed in video display 20, a four-point coordinate graphic element 62 for example in the form of a tetrahedron or cube structure in three-dimensional view may be superimposed in three-dimensional space on the stereo image display, providing a coordinate reference in the three-dimensional image space. To calibrate the position of a single manipulator with respect to its corresponding hand control, the system "opens" the control loop, and the operator 14 moves hand control 24, for example, while observing the motion of the tip of manipulator 32, steering the tip until it appears to be touching a first reference point 64 of superimposed graphic element 62, as shown in Fig. 6B. (Since the motion of the hand control and manipulator tip have not yet been coordinated, the alignment of the tip with the first reference point may require very deliberate effort.) The operator 14 then indicates to the system that superposition of manipulator and reference point has been achieved (e.g., a "set" signal is sent to the system).

The system then locks the manipulator 32 into place, opens the control loop by decoupling it from the hand control 24 and instructs the operator 14 to release the hand control 24. The system adjusts the extension  $L$  (Fig. 8 and 9) of the hand control to match that of the manipulator  $L'$ , by inserting the offset  $\sigma_3 = L - L'$ , so that when the control loop is closed, there will be no reactive motion by either device. That is, the apparent extension positions of the hand control 24 and manipulator 32 must be identical when compared in the control loop. The system then closes the control loop and unlocks the manipulator 32, returning control to the operator 14.



The operator then moves the hand control about its pivot point to an angular orientation  $(\Psi, \Omega)$  at which the operator senses that the image of the manipulator appears to emerge from the operator's hand control. Similar to the process described above, the system computes transformations which ensure that there will be no reactive motion by either master or slave when the control loop is closed. The system calculates angular offsets  $\sigma_1 = \Psi - \Psi'$  and  $\sigma_2 = \Omega - \Omega'$  and transforming the apparent position of the master or the slave prior to closing the control loop. The system now records the positions in three-dimensional space of the hand control master  $(\Psi_1, \Omega_1, L_1)$  and the manipulator slave  $(\Psi'_1, \Omega'_1, L'_1)$ .

The operator repeats the elements of this process with the remaining reference points of the superimposed graphic element 62. The system may then derive and install the following linearized equation relating incremental changes in the position of the hand control masters 24, 26 to incremental changes in the position of the manipulator slaves 32, 34, using the data sets to determine the coefficients of the equations relating the positions:

$$\begin{aligned}\Delta\Omega' &= k_{11}\Delta\Omega + k_{12}\Delta\Psi + k_{13}\Delta L \\ \Delta\Psi' &= k_{21}\Delta\Omega + k_{22}\Delta\Psi + k_{23}\Delta L \\ \Delta L' &= k_{31}\Delta\Omega + k_{32}\Delta\Psi + k_{33}\Delta L\end{aligned}$$

The solution to the above linearized equation is as follows:

$$\begin{vmatrix} k_{11} & k_{12} & k_{13} \\ k_{21} & k_{22} & k_{23} \\ k_{31} & k_{32} & k_{33} \end{vmatrix} = \begin{vmatrix} \Delta\Omega'_1 & \Delta\Omega'_2 & \Delta\Omega'_3 \\ \Delta\Psi'_1 & \Delta\Psi'_2 & \Delta\Psi'_3 \\ \Delta L'_1 & \Delta L'_2 & \Delta L'_3 \end{vmatrix} \begin{vmatrix} \Delta\Omega_1 & \Delta\Omega_2 & \Delta\Omega_3 \\ \Delta\Psi_1 & \Delta\Psi_2 & \Delta\Psi_3 \\ \Delta L_1 & \Delta L_2 & \Delta L_3 \end{vmatrix}^{-1}$$

(Eq. 3)

The system installs these coefficient values in the coordinate transformer 43 which controls servo 45, with appropriate offsets  $\sigma_1$ ,  $\sigma_2$  and  $\sigma_3$ , so that there is no reactive motion when the loop is closed.

In an alternative embodiment, calibration of the manipulators is achieved through virtual movement with the assistance of the system. Referring to Fig. 6B, the system moves manipulator tip 32, rather than the operator guiding the manipulator tip 32, to one of four defined points in the three-dimensional workspace 30, such as reference point 64 as seen by the operator. Using the hand control 24, the operator 14 then dynamically calibrates the position of the manipulator

32 by steering an overlaid graphic dot until it appears superimposed on the manipulator tip 32. The operator 14 then indicates to the system that superposition of manipulator tip 32 and reference point 64 has been achieved, and the coordinates of the manipulator 32 and hand control 24 are recorded. The process is repeated for the remaining reference points, after which the system derives and installs a coordinate transformation formula in the coordinate transformer 43, as described in the above embodiment.

In actual practice, it is preferable for the surgeon, rather than the system, to initiate the calibration process if the invention is being used in laparoscopic surgery. During surgery, the calibration process is being carried out within a patient's abdomen, where there is little room to maneuver. Hence, automatic movements of the manipulator, however small, may be considered less desirable than operator-controlled movements.

Another method for evoking a sense of telepresence in a telemanipulation system involves the use of a specific coordinate transformation to compensate for other changes in the displayed image, such as a lateral shift or a scale change. The camera may undergo a lateral or angular displacement, causing the displayed image to shift. In addition, the camera may be capable of magnifying the object in the workspace, which causes a scale change and a displacement of the apparent pivot point of the manipulator.

Figs. 7A and 7B show the combined effect of a lateral shift of the image and a scale change brought about by magnification of the image. Fig. 7A shows a portion of the displayed image, including a manipulator 32, in a two-dimensional field. The center of the image is at coordinates (0,0). The operator experiences the best possible sense of telepresence if the manipulator tip 72 at coordinates (u,v) in the image field appears to move as if it were rigidly attached to the control device in the operator's hand. The control device is pivoted at point (m,n) in the figure. The manipulator lies at an angle  $\alpha$  74 to the y-axis, and the

distance from pivot point (m,n) to manipulator tip (u,v) is length L 76.

Fig. 7B shows what the operator would see if the image were magnified by a factor M. The center of the image is shifted laterally by a distance of  $\Delta x$  and  $\Delta y$ , and the new apparent coordinates of the manipulator tip 72 are (u',v'). In order to ensure a desired level of telepresence, angle  $\alpha$  74 and length L 76 are remapped through perspective correction means 29 in the displayed image to give the operator the impression that the manipulator tip 72 is still rigidly attached to the hand control device. The following pair of equations describe the remapping of angle  $\alpha$  74 into angle  $\alpha'$  78 and length L 76 into length L' 80:

$$\alpha' = \arctan [(u' - m) / (v' - n)] \quad \text{and}$$

$$L' = [(u' - m)^2 + (v' - n)^2]^{\frac{1}{2}}$$

where:

$$u' = M(u - \Delta x) \quad v' = M(v - \Delta y) \quad \text{and where}$$

$$u = L(\sin \alpha) + m \quad v = L(\cos \alpha) + n$$

When  $\alpha$  and L are remapped according to the above equations, the manipulator tip 72 appears in the displayed image to move as if it were rigidly connected to the operator's hand control device.

The above relationships can be extended to include transformations in three dimensions in order to compensate for displacement of the manipulators when the camera lens 28 is rotated about its own visual axis 54, as in the embodiment described with respect to Fig. 3. In all cases, the desired goal of maintaining the perceived plane containing the two manipulators coincident with the plane of the two hand controls is achieved.

The invention has now been explained with reference to specific embodiments. Other embodiments will be apparent to those of ordinary skill in the art upon reference to the present description. For example, the invention can be extended to articulated manipulators with multiple points of rotation and translation or with pivot points at locations not physically attached to the manipulators. It is therefore not

intended that this invention be limited, except as indicated by the appended claims.

WHAT IS CLAIMED IS:

1           1. In a telemanipulation system for manipulating  
2 objects located in a workspace at a remote worksite by a  
3 control operator from a control operator station, said  
4 telemanipulation system including a manipulator means at the  
5 worksite with end effector means for manipulation of an object  
6 in the workspace, controller means including hand control  
7 means at the control operator station for remote control by  
8 the control operator of the manipulator means, image capture  
9 means for taking a real-time image of the workspace, and image  
10 producing means for producing a display on a monitor for eyes  
11 of the control operator, said controller means further  
12 comprising:

13               means coupled to said image capture means for  
14 processing the real-time image into a processed image for  
15 display to the control operator wherein said image capture  
16 means is at an angle and a position relative to the end  
17 effector means which differs from a relative position of eyes  
18 of the control operator and the hand control means, said image  
19 processing means correlating image of said end effector means  
20 with said hand control means.

1           2. The system according to claim 1 wherein said  
2 image processing means further comprises:

3               means for converting an actual position of the end  
4 effector means in the workspace to a perceived position of the  
5 end effector means in the viewable real-time image, the image  
6 capture means being monoscopic and being positioned at an  
7 angle  $\theta$  on a reference plane, said image capture means being  
8 above the reference plane in a reference space, and wherein  
9 the eyes of the control operator are positioned at an angle  $0^\circ$   
10 relative to a base line on said reference plane, said eyes  
11 being above said reference plane in said reference space, the  
12 viewable real-time image being rotated pixel-by-pixel by an  
13 angle  $\theta'$ , which is approximately equal to  $-\theta$ .

3. The system of claim 2, wherein coordinates of said perceived position of the end effector means are dynamically related to coordinates of said actual position of the end effector means by the following relationship:

$$\begin{bmatrix} p \\ q \\ r \end{bmatrix} = \begin{bmatrix} \cos\theta' & \sin\theta' & 0 \\ -\sin\theta' & \cos\theta' & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \cos\phi & 0 & \sin\phi \\ 0 & 1 & 0 \\ -\sin\phi & 0 & \cos\phi \end{bmatrix} \begin{bmatrix} \cos\theta & \sin\theta & 0 \\ -\sin\theta & \cos\theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \end{bmatrix}$$

where

[p,q,r] are coordinates of said perceived position,  
 [a,b,c] are coordinates of said actual position,  
 angle  $\theta$  is the rotation of the image capture means in a horizontal plane about a vertical axis,  
 angle  $\theta'$  being substantially equal to  $-\theta$ , and  
 angle  $\phi$  is the angle of declination below said vertical axis of an axis normal to a surface of the image capture means.

4. The system according to claim 1 wherein said image processing means further comprises:

means for static realignment of the manipulator means effected by rotating the image capture means about an axis normal to a surface of the image capture means to a position where each manipulator means appears in a viewable real-time image as presented to the control operator, where the hand controls are below a viewpoint of the control operator.

5. The system according to claim 1 wherein said image processing means further comprises:

means for static realignment of the manipulator means effected by rotating the image capture means about an axis normal to a surface of the image capture means to a position where the manipulator means appear in the viewable real-time image as presented to the control operator, where the hand controls are above a viewpoint of the control operator.

1           6.    The system according to claim 4 wherein the  
2   image capture means comprises:  
3           a monoscopic camera, wherein rotation of the image  
4   capture means is about a visual axis of said monoscopic camera  
   through a center of a lens of said monoscopic camera.

1           7.    The system according to claim 4 wherein the  
2   image capture means comprises:  
3           a stereoscopic dual aperture camera with a normal  
4   axis bisecting a line between each aperture of said  
5   stereoscopic camera, wherein rotation of the image capture  
6   means is about a visual axis of said stereoscopic camera  
7   through the center of said normal axis.

1           8.    The system according to claim 4 wherein said  
2   image processing means further comprises:  
3           means for translating an actual position of the end  
4   effector means in the workspace to a perceived position of the  
5   end effector means in the viewable real-time image such that  
6   motion of the end effector means appears rigidly connected to  
7   the hand control means.

1           9.    The system according to claim 8 wherein the  
2   translating of said actual position to said perceived position  
3   is according to the following relationship:

$$\begin{bmatrix} p \\ q \\ r \end{bmatrix} = \begin{bmatrix} \cos\Gamma & \sin\Gamma & 0 \\ -\sin\Gamma & \cos\Gamma & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \cos\Phi & 0 & \sin\Phi \\ 0 & 1 & 0 \\ -\sin\Phi & 0 & \cos\Phi \end{bmatrix} \begin{bmatrix} \cos\Theta & \sin\Theta & 0 \\ -\sin\Theta & \cos\Theta & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \end{bmatrix}$$

7   where

8       [p,q,r] are coordinates of said perceived position,  
9       [a,b,c] are coordinates of said actual position,  
10      angle  $\Gamma$  is the rotation of the image capture means about  
11      an axis normal to a surface of the image capture means,  
12      angle  $\Phi$  is the angle of declination of said normal axis  
13      below a vertical axis, and  
14      angle  $\Theta$  is the rotation of the image capture means in a  
15      horizontal plane about said vertical axis.

1           10. For use with a telemanipulation system for  
2 manipulating objects located in a workspace at a remote  
3 worksite by a control operator from a control operator  
4 station, said telemanipulation system including a manipulator  
5 means at the worksite with end effector means for manipulation  
6 of an object in the workspace, controller means including hand  
7 control means at the control operator station for remote  
8 control by the control operator of the manipulator means,  
9 image capture means for taking a real-time image of the  
10 workspace, and image producing means for reproducing a  
11 viewable real-time image on a monitor for eyes of the control  
12 operator, a method for dynamic calibration of the manipulator  
13 means through actual movement using a control loop wherein  
14 movements of the manipulator means directly follow movements  
15 of the hand control means, the method comprising the steps of:  
16           a) superimposing a representation of a four-point  
17 coordinate graphic element in three-dimensional space on the  
18 viewable real-time image;  
19           b) causing the hand control means to move to  
20 control motion of the end effector means; thereupon  
21           c) positioning the end effector means so that the  
22 end effector means appear to be touching a first reference  
23 point of said graphic element in the viewable real-time image;  
24           d) indicating to the system that superposition of  
25 the end effector means and said first reference point has been  
26 achieved;  
27           e) determining an offset by the relation  $\sigma_3 = L' -$   
28  $L$  to adjust the extension  $L$  of the hand control means to match  
29 the extension  $L'$  of the manipulator means;  
30           f) causing the hand control means to move about its  
31 pivot point to an angular orientation  $(\Psi, \Omega)$ , where the  
32 manipulator means in the viewable real-time image appears to  
33 emerge from the hand control means;  
34           g) determining offsets according to the  
35 relationships  $\sigma_1 = \Psi - \Psi'$  and  $\sigma_2 = \Omega - \Omega'$  for adjusting the  
36 angular orientation  $(\Psi, \Omega)$  of the hand control means to match  
37 the angular orientation  $(\Psi', \Omega')$  of the manipulator means;



- 38 h) recording a control position ( $\Psi, \Omega, L$ ) in three-  
 39 dimensional space of said hand control means;  
 40 i) recording a controlled position ( $\Psi', \Omega', L'$ ) in  
 41 three-dimensional space of said manipulator means  
 42 corresponding to the control position; and  
 43 j) repeating steps a) through i) for each remaining  
 44 reference point, thereby establishing calibration.

1 11. The method of claim 10 further comprising the  
 2 step of synchronizing incremental changes in position of the  
 3 hand control means to incremental changes in position of the  
 4 manipulator means according to the following set of equations:

$$\begin{aligned} \Delta\Omega' &\approx k_{11}\Delta\Omega + k_{12}\Delta\Psi + k_{13}\Delta L \\ \Delta\Psi' &\approx k_{21}\Delta\Omega + k_{22}\Delta\Psi + k_{23}\Delta L \\ \Delta L' &\approx k_{31}\Delta\Omega + k_{32}\Delta\Psi + k_{33}\Delta L \end{aligned}$$

8 whose solution is as follows:

$$\begin{vmatrix} k_{11} & k_{12} & k_{13} \\ k_{21} & k_{22} & k_{23} \\ k_{31} & k_{32} & k_{33} \end{vmatrix} \approx \begin{vmatrix} \Delta\Omega'_1 & \Delta\Omega'_2 & \Delta\Omega'_3 \\ \Delta\Psi'_1 & \Delta\Psi'_2 & \Delta\Psi'_3 \\ \Delta L'_1 & \Delta L'_2 & \Delta L'_3 \end{vmatrix} \begin{vmatrix} \Delta\Omega_1 & \Delta\Omega_2 & \Delta\Omega_3 \\ \Delta\Psi_1 & \Delta\Psi_2 & \Delta\Psi_3 \\ \Delta L_1 & \Delta L_2 & \Delta L_3 \end{vmatrix}^{-1}$$

1 12. For use with a telemanipulation system for  
 2 manipulating objects located in a workspace at a remote  
 3 worksite by a control operator from a control operator  
 4 station, said telemanipulation system including a manipulator  
 5 means at the worksite with end effector means for manipulation  
 6 of an object in the workspace, controller means including hand  
 7 control means at the control operator station for remote  
 8 control by the control operator of the manipulator means,  
 9 image capture means for taking a real-time image of the  
 10 workspace, and image producing means for reproducing a  
 11 viewable real-time image on a monitor for eyes of the control  
 12 operator, a method for dynamic calibration of the manipulator  
 13 means through virtual movement using a control loop where  
 14 movements of the manipulator means directly follow movements  
 15 of the hand control means, the method comprising the steps of:

1 a) causing the end effector means to move to a first  
 2 reference point of a selection of four points distributed in  
 3 three-dimensional space on the viewable real-time image;

4 b) manually moving the hand control means so that an  
 5 overlaid graphic dot appears superimposed on the viewable

6 image of the end effector means and said first reference  
7 point;

8 c) indicating to the system that superposition of  
9 the end effector means and said first reference point has been  
10 achieved;

11 d) calculating an offset  $\sigma_3 = L' - L$  to adjust the  
12 extension  $L$  of the hand control means to match the extension  
13  $L'$  of the manipulator means;

14 e) moving the hand control means about its pivot  
15 point to an angular orientation  $(\Psi, \Omega)$ , where the manipulator  
16 means in the viewable real-time image appears to emerge from  
17 the hand control means;

18 f) calculating offsets  $\sigma_1 = \Psi - \Psi'$  and  $\sigma_2 = \Omega - \Omega'$   
19 to adjust the angular orientation  $(\Psi, \Omega)$  of the hand control  
20 means to match the angular orientation  $(\Psi', \Omega')$  of the  
21 manipulator means;

22 g) recording a position  $(\Psi, \Omega, L)$  in three-dimensional  
23 space of said hand control means;

24 h) recording a position  $(\Psi', \Omega', L')$  in three-  
25 dimensional space of said manipulator means; and

26 i) repeating steps a) through h) for each remaining  
27 reference point, thereby establishing calibration.

1 13. The method of claim 12 further comprising the  
2 step of relating incremental changes in position of the hand  
3 control means to incremental changes in position of the  
4 manipulator means according to the following set of equations:

$$\begin{aligned} \Delta\Omega' &\approx k_{11}\Delta\Omega + k_{12}\Delta\Psi + k_{13}\Delta L \\ \Delta\Psi' &\approx k_{21}\Delta\Omega + k_{22}\Delta\Psi + k_{23}\Delta L \\ \Delta L' &\approx k_{31}\Delta\Omega + k_{32}\Delta\Psi + k_{33}\Delta L \end{aligned}$$

8 whose solution is as follows:

$$\begin{vmatrix} k_{11} & k_{12} & k_{13} \\ k_{21} & k_{22} & k_{23} \\ k_{31} & k_{32} & k_{33} \end{vmatrix} \approx \begin{vmatrix} \Delta\Omega'_1 & \Delta\Omega'_2 & \Delta\Omega'_3 \\ \Delta\Psi'_1 & \Delta\Psi'_2 & \Delta\Psi'_3 \\ \Delta L'_1 & \Delta L'_2 & \Delta L'_3 \end{vmatrix} \begin{vmatrix} \Delta\Omega_1 & \Delta\Omega_2 & \Delta\Omega_3 \\ \Delta\Psi_1 & \Delta\Psi_2 & \Delta\Psi_3 \\ \Delta L_1 & \Delta L_2 & \Delta L_3 \end{vmatrix}^{-1}$$

1 14. In a telemanipulation system for manipulating  
2 objects located in a workspace at a remote worksite by a  
3 control operator from a control operator station, said  
4 telemanipulation system including a manipulator means at the

5 remote worksite with end effector means for manipulation of an  
 6 object in the workspace, controller means including hand  
 7 control means at the control operator station for remote  
 8 control by the control operator of the manipulator means,  
 9 image capture means for taking a real-time image of the  
 10 workspace, and image producing means for producing a display  
 11 on a monitor for eyes of the control operator, control means  
 12 comprising:

13 means coupled to said image capture means for  
 14 processing the real-time into a processed image for display to  
 15 the control operator wherein said image capture means is at an  
 16 angle and a position relative to the end effector means which  
 17 differs from a relative position of eyes of the control  
 18 operator and the hand control means, and which further differs  
 19 in scale and in lateral position, said image processing means  
 20 correlating manipulation of said end effector means with said  
 21 hand control means, said image processing means further  
 22 comprising:

23 means for performing a perspective correction in the  
 24 viewable real-time image following a lateral shift and a scale  
 25 change of the image capture means.

1 15. The system according to claim 14 wherein said  
 2 perspective correction means comprises means for performing  
 3 transformations according to the following relationships:

$$\begin{aligned} 4 \quad \alpha' &= \arctan [(x' - m) / (y' - n)], \\ 5 \quad L' &= [(x' - m)^2 + (y' - n)^2]^{1/2}, \\ 6 \quad x' &= M(x - \Delta x), \\ 7 \quad y' &= M(y - \Delta y), \\ 8 \quad x &= L(\sin \alpha) + m, \\ 9 \quad y &= L(\cos \alpha) + n \end{aligned}$$

10 where

11 coordinates (m,n) describe a position of a pivot  
 12 point of the manipulator means before said lateral shift and  
 13 said scale change occur,

14 coordinates (m',n') describe a position of said  
 15 pivot point of the manipulator means after said lateral shift  
 16 and said scale change occur,

17 coordinates (x,y) describe a position of the end  
18 effector means before said lateral shift and said scale change  
19 occur,  
20 coordinates (x',y') describe a position of the end  
21 effector means after said lateral shift and said scale change  
22 occur,  
23 coordinates ( $\Delta x, \Delta y$ ) describe the change in position  
24 of the end effector means brought about by said lateral shift,  
25 factor M describes the magnification factor of said  
26 scale change,  
27 angle  $\alpha$  is the rotation of the manipulator means  
28 about a vertical axis before said lateral shift and said scale  
29 change occur,  
30 angle  $\alpha'$  is the rotation of the manipulator means  
31 about said vertical axis after said lateral shift and said  
32 scale change occur,  
33 length L is a distance between said pivot point and  
34 the end effector means before said lateral shift and said  
35 scale change occur, and  
36 length L' is a distance between said pivot point and  
37 the end effector means after said lateral shift and said scale  
38 change occur.

16. In a telemanipulation system for manipulating  
1 objects located in a workspace at a remote worksite by a  
2 control operator from a control operator station, said  
3 telemanipulation system including manipulator means at the  
4 worksite with end effector means for manipulation of an object  
5 in the workspace, controller means including hand control  
6 means at the control operator station for remote control by  
7 the control operator of the manipulator means, image capture  
8 means for taking a real-time image of the workspace, and image  
9 producing means for producing a display on a monitor for eyes  
10 of the control operator, said controller means further  
11 comprising:  
12 means coupled to said image capture means for  
13 processing the real-time image into a processed image for

14 display to the control operator wherein said image capture  
15 means is at an angle and a position relative to the end  
16 effector means which differs from a relative position of eyes  
17 of the control operator and the hand control means, said image  
18 processing means correlating image of said end effector means  
19 with said hand control means;

20 servo control means for controlling position of said  
21 manipulator means;

22 first position sensing means coupled for sensing  
23 position of said manipulator means in said workspace;

24 second position sensing means coupled for sensing  
25 position of said hand control means at the operator station;  
26 and

27 coordinate transformation means coupled to said  
28 image processing means, to said first position sensing means  
29 and to said second position sensing means for transforming  
30 information about manipulator position, hand control position  
31 and processed image position and into control signals applied  
32 to said servo control means.

1 17. The apparatus according to claim 16 further  
2 including:

3 third position sensing means coupled to said image  
4 capture means for sensing position of said image capture means  
5 at the worksite; and wherein

6 said coordinate transformation means is coupled to  
7 said third position sensing means for transforming position  
8 information about said image capture means into said control  
9 signals.

1 18. For use with a telemanipulation system for  
2 manipulating objects located in a workspace at a remote  
3 worksite by a control operator from a control operator  
4 station, said telemanipulation system including a manipulator  
5 means at the worksite with end effector means for manipulation  
6 of an object in the workspace, controller means including hand  
7 control means at the control operator station for remote  
8 control by the control operator of the manipulator means,

9 image capture means for taking a real-time image of the  
10 workspace, and image producing means for reproducing a  
11 viewable real-time image on a monitor for eyes of the control  
12 operator, a method for dynamic calibration of the manipulator  
13 means through actual movement using a control loop wherein  
14 movements of the manipulator means directly follow movements  
15 of the hand control means, the method comprising the steps of:  
16 superimposing a representation of a four-point  
17 coordinate graphic element in three-dimensional space on the  
18 real-time image;  
19 causing the hand control means to move; thereupon  
20 positioning the end effector means under control of  
21 the hand control means so that the end effector means appears  
22 to be touching reference points of said graphic element in the  
23 real-time image; and  
24 establishing a tracking relationship between the  
25 hand control means and the end effector means, thereby  
26 establishing calibration.

1 19. For use with a telemanipulation system for  
2 manipulating objects located in a workspace at a remote  
3 worksite by a control operator from a control operator  
4 station, said telemanipulation system including a manipulator  
5 means at the worksite with end effector means for manipulation  
6 of an object in the workspace, controller means including hand  
7 control means at the control operator station for remote  
8 control by the control operator of the manipulator means,  
9 image capture means for taking a real-time image of the  
10 workspace, and image producing means for reproducing a  
11 viewable real-time image on a monitor for eyes of the control  
12 operator, a method for dynamic calibration of the manipulator  
13 means through virtual movement using a control loop where  
14 movements of the manipulator means directly follow movements  
15 of the hand control means, the method comprising the steps of:  
16 automatically causing the end effector means to move  
17 through a preselected sequence of reference points distributed  
18 in three-dimensional space on the viewable real-time image;

19                   manually moving the hand control means so that an  
20 overlaid graphic dot appears superimposed on the viewable  
21 image of the end effector means at each of said reference  
22 points;

23                   registering position of the hand control means at  
24 the position of each reference point; and

25                   establishing a tracking relationship between the  
26 hand control means and the end effector means, thereby  
27 establishing calibration.





FIG. 1A.








FIG. 2.





FIG. 4.

417



**FIG. 3.**

5/7




FIG. 6A.




FIG. 6B.




FIG. 5A.




FIG. 5B.

6/7




FIG. 7A.




FIG. 7B.

7/7




FIG. 8.




FIG. 9.

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US95/05669

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>																				
IPC(6) : G06K 9/00; A61B 1/00																				
US CL : Please See Extra Sheet																				
According to International Patent Classification (IPC) or to both national classification and IPC																				
<b>B. FIELDS SEARCHED</b>																				
Minimum documentation searched (classification system followed by classification symbols)																				
U.S. : 382/128, 153, 293, 295; 348/65; 364/413.13, 413.22; 128/4, 6; 395/95, 137, 138, 924																				
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched																				
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)																				
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>																				
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.																		
X -- Y	US, A, 5,182,641 (DINER ET AL) 26 January 1993, col.2, lines 40-48 and col.5, lines 3-23, col.5, lines 46-56 and col.8, lines 20-35.	1 ----- 4-8, 14, 16, 17																		
X --, Y	US, A, 5,368,015 (WILK) 29 November 1995, col.10, lines 20-32 and col.10, lines 42-47.	1, 14 ----- 2-7, 15-17																		
Y,P	US, A, 5,339,799 (KAMI ET AL) 23 August 1994, col.21, lines 23-37 and col.22, lines 36-51.	1, 14-17																		
A	US, A, 4,853,874 (IWAMOTO ET AL) 01 August 1989, see abstract.	3, 8, 9, 15-17																		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.																				
<table border="0"> <tr> <td>* Special categories of cited documents:</td> <td>"T"</td> <td>later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>"A" document defining the general state of the art which is not considered to be part of particular relevance</td> <td>"X"</td> <td>document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>"E" earlier document published on or after the international filing date</td> <td>"Y"</td> <td>document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>"A"</td> <td>document member of the same patent family</td> </tr> <tr> <td>"O" document referring to an oral disclosure, use, exhibition or other means</td> <td></td> <td></td> </tr> <tr> <td>"P" document published prior to the international filing date but later than the priority date claimed</td> <td></td> <td></td> </tr> </table>			* Special categories of cited documents:	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	"A" document defining the general state of the art which is not considered to be part of particular relevance	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	"E" earlier document published on or after the international filing date	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"A"	document member of the same patent family	"O" document referring to an oral disclosure, use, exhibition or other means			"P" document published prior to the international filing date but later than the priority date claimed		
* Special categories of cited documents:	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention																		
"A" document defining the general state of the art which is not considered to be part of particular relevance	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone																		
"E" earlier document published on or after the international filing date	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art																		
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"A"	document member of the same patent family																		
"O" document referring to an oral disclosure, use, exhibition or other means																				
"P" document published prior to the international filing date but later than the priority date claimed																				
Date of the actual completion of the international search		Date of mailing of the international search report																		
15 JUNE 1995		07 SEP 1995																		
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231		Authorized officer <i>B. H. Kelley</i> CHRISTOPHER KELLEY																		
Facsimile No. (703) 305-3230		Telephone No. (703) 305-9646																		

**INTERNATIONAL SEARCH REPORT**International application No.  
PCT/US95/05669**C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	IEEE Engineering in Medicine Conference, June 1989, Bergamasco et al, "Advanced Interfaces for Teleoperated Biomedical Robots" first page col.2.	1, 14
Y	Proceedings of the First CISM-ITOMM Symposium, Vol.1, 08 September 1973, Alexander, Arthur, "Impacts of Telemation on Modern Society", pages 122-136, especially page 132.	1, 14



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/05669

### A. CLASSIFICATION OF SUBJECT MATTER:

US CL :

382/128, 153, 293, 296; 348/65; 364/413.13, 413.22; 128/4, 6; 395/95, 137, 138, 924

### BOX II. OBSERVATIONS WHERE UNITY OF INVENTION WAS LACKING

This ISA found multiple inventions as follows:

Group I Claims 1-9 and 14-17, drawn to the relation between the position of the operation and the end effector of telemanipulation system. (Class 382/293)

Group II Claims 10-13 and 18-19, drawn to a dynamic calibration system and method for establishing a tracking relationship between an end effector and the hand control. (Class 395/152)

The claims of these two groups are directed toward different invention which are not linked to form a single general concept. The claims in the different groups do not have in common the same or corresponding "special technical features".

In particular, the apparatus and processing (such as manually moving the control means so a graphic dot is superimposed on the screen) require different searches.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**